

WOER  **Flexible Thick Adhesive Lined Dual Wall Heat Shrinkable Tube**
Type: SBRS-(3X)GLW

**Description:****Flexible, Thick Adhesive Lined Dual Wall Heat Shrinkable Tube**

Flexible, Thick Adhesive Lined Dual Wall Heat Shrinkable Tube is manufactured by co-extrusion of polyolefin and hot-melt adhesive. Designed to provide both insulation and sealing for protected articles. Used to protect bundles wires and metal tubes against water and moisture.

Features:

1. Flexible, thick adhesive lined to bond to a wide variety of plastics, rubber and metals
2. Operating Temperature: -45°C~125°C
3. Shrinking Temperature: Start at 70°C, and shrunk totally at 125°C
4. Shrink Ratio: 3:1

Dimension

Model	Inch	As Supplied	After Recovery (mm)			Standard package (m/spool)
		Inner diameter	Total wall thickness	Wall thickness of adhesive layer	Inner diameter	
		Internal Diameter (mm)				
SBRS-(3X)GLW 3.2MM	1/8	3.2	0.95±0.15	0.40±0.10	1.0	200
SBRS-(3X)GLW 4.8MM	3/16	4.8	1.10±0.15	0.40±0.10	1.6	100
SBRS-(3X)GLW 6.4MM	1/4	6.4	1.20±0.15	0.50±0.12	2.2	100
SBRS-(3X)GLW 7.9MM	5/16	7.9	1.35±0.15	0.50±0.12	2.7	100
SBRS-(3X)GLW 9.5MM	3/8	9.5	1.45±0.20	0.50±0.12	3.2	50
SBRS-(3X)GLW 12.7MM	1/2	12.7	1.70±0.20	0.55±0.15	4.2	1.0m or 25m
SBRS-(3X)GLW 15.0MM	5/8	15.0	1.80±0.20	0.55±0.15	5.2	1.0m or 25m
SBRS-(3X)GLW 19.1MM	3/4	19.1	2.00±0.20	0.55±0.15	6.3	1.0m or 25m
SBRS-(3X)GLW 25.4MM	1	25.4	2.10±0.25	0.55±0.15	8.5	1.0m or 25m
SBRS-(3X)GLW 39.0MM	1-1/2	39.0	2.40±0.25	0.60±0.15	13.5	1.0m or 25m